

GÜVEN SOĞUTMA
ÜNİTELERİ SAN. VE TİC. A.Ş.

Add: Hastane Mah. Hadimköy İstanbul Cd. No:78/1
 34555, Arnavutköy, İstanbul, TURKEY
 Tel: +90 212 771 51 12 - 771 51 13
 Fax: +90 212 771 51 10
 www.gvn.com.tr



GVN STANDART PRODUCT **Customer**

VERTICAL LIQUID RECEIVERS **Product**

V8A.33B.30.C6.C6.F4.H31.F4 **Code**

Customer Code

DESIGN DATA

Capacity [Lt.]	30 Lt.
Design Pressure [PS]	33 Bar
Pneumatic Test Pressure [PT]	36 Bar
Hydraulic Test Pressure	48 Bar
Design Temperature [TS]	Min.-20C / Max.+130C
Cooler Fluid Type	HFC-CFC-HCFC
Fluid Group	2
Category	CAT II / D1
Desing Calculation	EN 14276-1/EN 13445-3
Welded Joint Efficiency	0.85
Material Group (Shell / Head)	1.2
Testing Group	3b
Corrasion Allowance	0,5 mm
Ndt	10%
Packaging Size & Weight	00*00*00 & 00 Kg.
Drawed By	H.DALSIZ
Approved By	D.GÜL
Date	20.02.2024
Color	RAL 5009

MATERIAL DATA

No	Connection	Model	Code	Material	Qty
1	Inlet Connection	ROT. 1 1/4" H:27	106.060.A03.001.001	E275	1
2	Inlet Valve	RV.45b 7/8	C6.RV.45B.1 1-4-7-8--		1
3	Outlet Connection	ROT. 1 1/4" H:27	106.060.A03.001.001	E275	1
4	Outlet Valve	RV.45b 7/8	C6.RV.45B.1 1-4-7-8--		1
5	Safety Valve Conn.	NPT 1/2" H:18	106.060.F04.000.001	E275-ST44	1
6	Blind Plug	NPT 1/2" Plug	106.130.F04.001.001	S235JR	2
7	Level Sensor Conn.	NPT 1/2" H:18	106.060.F04.000.001	S235JR	1
8	Sight Glass Type Conn.	SG-SW38 H:27	106.0SW.038.001.001	E275	2
9	Sight Glass	SW38	SW-38	E275	2
10	Shell	Ø273x4 H:390	204.V08.33B.030.019	EN10217-3 P355NH	1
11	Head Torispheric	Ø273x4 H:95	201.045.273.001.001	EN10028-2 P355GH	1
12	Head - Torispheric	Ø273x4 H:95	101.045.273.001.000	P355GH EN10028-2	1
13	Pipe	Ø19X1,5	204.A19.015.000.180	EN10297-1 E235	1
14	Skirt With	Ø247x2,5 H:18	105.004.247.001.001	DD13	1

GENERAL NOTES

- Max. allowable operating pressure (PS) according to the temperature range;
- 1) Allowable operating temperature : min. -20C° / max. +130C° PS1 = 33 Bar
- 2) Allowable operating temperature : min. -40C° / max. -20C° PS2 = 24 Bar
- Unless otherwise specified dimensions in MM
- Unless otherwise specified do not scale
- Unless otherwise specified tube must be clean&free from burrs inside&outside& suitable for soldering
- Unless otherwise specified do not scale indicated thickness are min. after forming or machining
- Unless otherwise specified dimension tolerances according to EN 113445-4

REVISIONS

No	Details Of Change	Date	By
01			
02			
03			

RELATED DRAWINGS

No	Description	Drawing No
01		
02		



We reserve all rights in this document and in the information contained therein. Reproduction use or disclosure to third parties without express authority is strictly forbidden.

