



## DECLARATION OF PERFORMANCE

(REGULATION (EU) No 305/2011/CE)

0497/CPR/5589-2024

1) Unique identification code of the product type:

**ZETACELL B**

2) Type:

**Thickness 3-13 mm**

3) Purpose of the construction product in accordance with: EN 14313:2009+A1:2013

**Sheet / Sheath Cross-linked polyethylene foam PEF  
to be used as thermal insulation in residential, civil and industrial systems and installations**

4) Manufacture

**ZETAESSE S.p.A.**  
**Via Vicenza 45 - 31050 Vedelago (TV) - Italy**  
**Tel. +39 0423 400621 – <http://www.zetaesse.it>**

5) System or systems for evaluating and verifying the constancy of the performance of the construction product according to Annex V of Regulation 305/2011 / EC as determined by the harmonized technical specification EN 14313:2009+A1:2013,

**SISTEMA 1**

Certified by : CSI S.p.A. - 0497

The performance of the product identified by points 1, 2 and 3 are in conformity with the statements in the table below

Caratteristiche principali		Prestazioni	Specifica Tecnica Armonizzata
Thermal resistance	Thermal Conductivity 3mm 0-10-40°C	$\lambda = 0.0356-0.0370-0.0411$	<b>EN 14313:2009+A1:2013</b>
	Thermal Conductivity 11mm 0-10-40°C	$\lambda = 0.0380-0.0395-0.0445$	
Dimensions and tolerances		$d_b = 3-13 \text{ mm}$	
Reaction to fire (Euroclass) (3-13mm)		B-s2, d0	
Operating temperature	Max	NPD	
	Min	NPD	
Water permeability	Water absorption (UNI EN 12087)	NPD	
Water vapour permeability	Water vapour diffusion resistance factor (3-13mm) without film	MU 1100- 3000	
	Water absorption	NPD	
Sostanze corrosive rilasciate		NPD	
Release of dangerous substances to indoor environment		NPD	
Continuous glowing combustion		NPD	

The performance of the product indicated above in points 1 and 2 is in conformity with the declared performance in point 5. This makes this declaration of performance in the sole responsibility of the manufacturer referred to in point 4.

**ZETAESSE S.p.A.**  
Pasotti Enrico, C.E.O.