

## Coils ASC3 and Cable Assemblies

### Standards

- ASC3 Coils and cable assemblies conform to Low Voltage Directive



ASC3

Type	Part No.	Voltage	Power Input	Electr. Connection	Protection
ASC3 230V / 50 (60) Hz	<b>801 077</b>	AC	8 W	without plug see cable assemblies	IP65 with plug / cable assembly
ASC3 120V / 50 (60) Hz	<b>801 078</b>				
ASC3 24V / 50 (60) Hz	<b>801 079</b>				
ASC3 24V DC	<b>801 076</b>	DC	17 W		
DS2-N15 + ASC3 24VAC	<b>804 620 + 801 079</b>	DC	3 W	with plug and cable assembly	IP65

Note: Coils are delivered with retainer kit.  
Please order cable assemblies separately.



ASC-N15

### Cable Assemblies for ASC Coils

Type	Part No.	Temperature Range	Cable length	Wire diameter	Connector Type
ASC-N15	<b>804 570</b>	-50 .. +80°C for stationary use only	1.5m	3 x 0.75 mm <sup>2</sup>	loose wires
ASC-N30	<b>804 571</b>		3.0m		
ASC-N60	<b>804 572</b>		6.0m		



DS2-N15 ASC3 24V

### Cable Assembly with 24V DC Chopper Plug

- Enables standard 24V AC Coil to be used for DC applications
- Low power assumption (3W only)
- No MOPD degradation

Type	Part No.	Temperature Range	Cable length	Wire diameter	Connector Type
DS2-N15	<b>804 620</b>	-25 .. +80°C	1.5 m	2 x 0.75 mm <sup>2</sup>	loose wires

### Other Accessories for Solenoid Valves

Type	Part No.	Description
X 11981-1	<b>027 451</b>	Service tool for 110RB. 240RA. 540RA. 3031
ASC3-K01	<b>801 080</b>	Retainer kit (one cap + two O-rings)
PG9 Plug	<b>801 012</b>	Plug according to EN 175301 with cable gland PG 9
PG11 Plug	<b>801 013</b>	Plug according to EN 175301 with cable gland PG 11