



018F6707 🗠

Solenoid coil, BE024AS, Terminal box, 24 V

Electrical connection: Terminal box, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67, Packing format: Multi pack

PRODUCT DETAILS

TRODUCT DETAILS	
Gross weight	0.32 kg
Net weight	0.31 kg
EAN	5702428519120
Actuator size	13.5 mm
Ambient temperature range [°C]	80 ℃
[Max]	
Ambient temperature range [°C]	-40 °C
[Min]	
Ambient temperature range [°F]	175 °F
[Max]	
Ambient temperature range [°F]	-40 °F
[Min]	
Approval	LLC CDC TYSK
Cable diameter [mm] [Max]	11 mm
Cable diameter [mm] [Min]	6 mm
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Conductor area [mm2]	0.75 - 1.5 mm2
Duty rating	Continuous
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Enclosure rating IP	IP67
Frequency [Hz]	50 Hz
Identical product	018F8707
Packing format	Multi pack
Parts Program name	EV210B
	EV212B
	EV220B 15 - 50
	EV220B 6 - 22
	EV220B 65 - 100
	EV222B
	EV224B
	EV227B
	EV250B
	EV251B

PRODUCT DETAILS

Power consumption 50Hz [VA]	21 VA
Power consumption [W] 50Hz	12 W
Product accessories	Solenoid coil accessories
Product group	Solenoid valves
Product name	Solenoid coil
Quantity per packing format	32 pc
Rel. Humidity [% RH] [Max]	100 %
Rel. Humidity [% RH] [Min]	0 %
Serviceable	No
Spare part number	018F6182
Supply voltage 50Hz Max [V]	24 V
Supply voltage [V] AC	24 V
Туре	BE024AS
Type designation	BE024AS

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Spare Parts

	016D3330 Z Solenoid valve, EV220B, Flange, 2 1/2 in, NBR, NC Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2
	016D3331 2 Solenoid valve, EV220B, Flange, 3 in, NBR, NC Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2
Ļ	032H8041 C Solenoid valve, EV210A, G, 1/4, FKM, NC Body material: Stainless steel, Operation: Direct-operated, Number of ways: 2/2
Ť	032U1200 ≥ Solenoid valve, EV210B, G, 1/8, NBR, NC Approval: DNVGL-CG-0339; GL, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
; ;;	032U145802 Solenoid valve, EV210B, G, 1/8, FKM, NC Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
₿₽	032U145831 2 Solenoid valve, EV210B, G, 1/8, FKM, NC Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

e Parts	
	032U147002 🖻
	Solenoid valve, EV210B, G, 1/4, FKM, NC
	Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U147016 2
	Solenoid valve, EV210B, G, 1/4, FKM, NC
10	Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U147031 🗠
	Solenoid valve, EV210B, G, 1/4, FKM, NC
10	Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U148002 🖻
	Solenoid valve, EV210B, G, 3/8, FKM, NC
	Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U148016 🖻
	Solenoid valve, EV210B, G, 3/8, FKM, NC
1	Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U148031 🗠
	Solenoid valve, EV210B, G, 3/8, FKM, NC
	Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3601 ⊠
	Solenoid valve, EV210B, G, 1/4, FKM, NC
	Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3605 ⊵
	Solenoid valve, EV210B, G, 3/8, EPDM, NC
	Approval: ACS, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3607 ⊠
	Solenoid valve, EV210B, G, 3/8, EPDM, NC
.	Approval: ACS; DNVGL-CG-0339; GL, Body material: Brass, Operation: Direct-operated, Number of ways 2/2
	032U3615 ⊠
1	Coloradore EV210D C 1/2 EDDM NC
T	Solenoid valve, EV210B, G, 1/2, EPDM, NC

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



	032U3616 🗈
1	Solenoid valve, EV210B, G, 1/2, FKM, NC
	Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3617 🗠
	Solenoid valve, EV210B, G, 1/2, EPDM, NC
	Approval: ACS; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2,
	032U3619 🛚
Ţ	Solenoid valve, EV210B, G, 1/2, EPDM, NC
	Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2
8	032U3621 🛛
4	Solenoid valve, EV210B, G, 3/4, EPDM, NC
	Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2
9	032U3623 🖻
	Solenoid valve, EV210B, G, 1, EPDM, NC
	Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2
	032U3630 🛙
1	Solenoid valve, EV210B, G, 1/8, EPDM, NO
	Approval: ACS; DNVGL-CG-0339; PZH, Body material: Brass, Operation: Direct-operated, Number of
	ways: 2/2
	032U3632 🗷
	Solenoid valve, EV210B, G, 1/8, EPDM, NO
	Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
	032U3633 🖻
1	Solenoid valve, EV210B, G, 1/8, FKM, NO
*	Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3634 ⊵
L	Solenoid valve, EV210B, G, 1/8, EPDM, NO
*	Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
	032U3635 🖻
1	Solenoid valve, EV210B, G, 1/8, FKM, NO
Contra Co	Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

1	032U3636 Solenoid valve, EV210B, G, 1/4, EPDM, NO Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
1 a	032U3637 2 Solenoid valve, EV210B, G, 1/4, FKM, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	O32U3638 Solenoid valve, EV210B, G, 1/4, EPDM, NO Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
Ť	032U3640 ≥ Solenoid valve, EV210B, G, 1/4, EPDM, NO Approval: ACS, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
1	032U3641 ≥ Solenoid valve, EV210B, G, 1/4, FKM, NO Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
	032U3642 ⊠ Solenoid valve, EV210B, G, 3/8, EPDM, NC Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
1	032U5352 ≥ Solenoid valve, EV250B, G, 1/2, EPDM, NO Approval: ACS; DNVGL-CG-0339; GL; PZH; SINTEF, Body material: DZR brass, Operation: Assisted lift operated, Number of ways: 2/2
Ť	032U5701 Solenoid valve, EV210B, G, 1/8, EPDM, NC Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
Ť	032U5702 № Solenoid valve, EV210B, G, 1/8, FKM, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

1	032U5705 ≥ Solenoid valve, EV210B, G, 1/8, EPDM, NC Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
Ť	032U5706 № Solenoid valve, EV210B, G, 1/8, FKM, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2
ļ	032U5707 № Solenoid valve, EV210B, G, 1/4, EPDM, NC Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
	032U5709 ≥ Solenoid valve, EV210B, G, 1/4, EPDM, NC Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number o ways: 2/2
5	032U5815 ≥ Solenoid valve, EV220B, G, 1/2, EPDM, NC Approval: PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U5820 Solenoid valve, EV220B, G, 3/4, EPDM, NC Approval: PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U5832 ⊵ Solenoid valve, EV220B, G, 1 1/4, EPDM, NC Approval: CE; PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U5840 Solenoid valve, EV220B, G, 1 1/2, EPDM, NC Approval: CE; PZH; SINTEF, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U5850 ≥ Solenoid valve, EV220B, G, 2, EPDM, NC Approval: CE; PZH; SINTEF, Body material: DZR brass, Operation: Servo-operated (diaphragm), Numbe of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

	032U7170 Solenoid valve, EV220B, G, 1/2, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
1	032U7171 ≥ Solenoid valve, EV220B, G, 3/4, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U7172 ≥ Solenoid valve, EV220B, G, 1, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
5	O32U7173 ☑ Solenoid valve, EV220B, G, 1 1/4, NBR, NC Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number o ways: 2/2
	032U7174 ≥ Solenoid valve, EV220B, G, 1 1/2, NBR, NC Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number o ways: 2/2
5	032U7175 Solenoid valve, EV220B, G, 2, NBR, NC Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U7180 ≥ Solenoid valve, EV220B, G, 1/2, NBR, NO Approval: DNVGL-CG-0339; EAC; LLC CDC EURO-TYSK; UL, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U7181 전 Solenoid valve, EV220B, G, 3/4, NBR, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
500	032U7182 № Solenoid valve, EV220B, G, 1, NBR, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

5	032U7183 ☑ Solenoid valve, EV220B, G, 1 1/4, NBR, NO Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number ways: 2/2
5	O32U7184 Solenoid valve, EV220B, G, 1 1/2, NBR, NO Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number ways: 2/2
	032U7185 Solenoid valve, EV220B, G, 2, NBR, NO Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number ways: 2/2
	O32U8360 Solenoid valve, EV224B, G, 1/2, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	O32U8361 ☑ Solenoid valve, EV224B, G, 1/2, NBR, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8362 Solenoid valve, EV224B, G, 3/4, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8363 Solenoid valve, EV224B, G, 3/4, NBR, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8364 ≥ Solenoid valve, EV224B, G, 1, NBR, NC Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2
-	O32U8365 ▷ Solenoid valve, EV224B, G, 1, NBR, NO Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



	032U8500 ⊠ Solenoid valve, EV220B, G, 1/2, EPDM, NC Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8501 ⊠ Solenoid valve, EV220B, G, 3/4, EPDM, NC Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8502 IZ Solenoid valve, EV220B, G, 1, EPDM, NC Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8503 ⊠ Solenoid valve, EV220B, G, 1 1/4, EPDM, NC Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8504 № Solenoid valve, EV220B, G, 1 1/2, EPDM, NC Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
5	032U8505 ≥ Solenoid valve, EV220B, G, 2, EPDM, NC Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
ļ.,	032U8506 ⊠ Solenoid valve, EV220B, G, 1/2, FKM, NC Approval: DNV; EAC; UL, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8507 ≥ Solenoid valve, EV220B, G, 3/4, FKM, NC Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
	032U8508 ☑ Solenoid valve, EV220B, G, 1, FKM, NC Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



Spare Parts

032U8509 또 Solenoid valve, EV220B, G, 1 1/4, FKM, NC Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
032U8510 ≥ Solenoid valve, EV220B, G, 1 1/2, FKM, NC Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2
032U8511 № Solenoid valve, EV220B, G, 2, FKM, NC Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈