

**018F6802****Solenoid coil, BG240AS, Terminal box, 240 V**

Electrical connection: Terminal box, Supply voltage [V] AC: 240, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67, Packing format: Multi pack

PRODUCT DETAILS

Gross weight	0.51 kg
Net weight	0.49 kg
EAN	5702428027809
Actuator size	13.5 mm
Ambient temperature range [°C] [Max]	80 °C
Ambient temperature range [°C] [Min]	-40 °C
Ambient temperature range [°F] [Max]	175 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	LLC CDC TYSK CE EAC UKCA
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Duty rating	Continuous
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Electrical connector	Screwed cable entry
Enclosure rating IP	IP67
Frequency [Hz]	50 Hz
Further information	Terminal box
Packing format	Multi pack
Parts Program name	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV250B
Power consumption 50Hz [VA]	25 VA

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Solenoid coil, BG240AS, Terminal box, 240 V**PRODUCT DETAILS**

Power consumption [W] 50Hz	13 W
Product accessories	Solenoid coil accessories
Product group	Solenoid valves
Product name	Solenoid coil
Quantity per packing format	24 pc
Rel. Humidity [% RH] [Max]	100 %
Rel. Humidity [% RH] [Min]	0 %
Serviceable	No
Spare part number	018F6802
Supply voltage 50Hz Max [V]	240 V
Supply voltage [V] AC	240 V
Type	BG240AS
Type designation	BG240AS

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)