



077B7003 🖻

Service thermostat, B62

Type: B62, Type designation: Service thermostat, Used for product: Refrigerators; with automatic defrost, Warm cut-in [°C]: 3.5, Warm cut-out [°C]: -11.0, Cold cut-out [°C]: -27.5, Capillary tube length [mm]: 1600

PRODUCT DETAILS

| Gross weight | 0.15 kg |
|-----------------------------|--------------------------|
| Net weight | 0.12 kg |
| EAN | 5702424006570 |
| Approval | CE |
| | СМІМ |
| | BEAB |
| | EAC |
| | LLC CDC TYSK |
| | cURus |
| Capillary tube length [in] | 63 in |
| Capillary tube length [mm] | 1600 mm |
| Cold cut-in [°C] | 3.5 ℃ |
| Cold cut-in [°F] | 38.3 °F |
| Cold cut-out [°C] | -27.5 °C |
| Cold cut-out [°F] | -17.5 °F |
| Packing format | Multi pack |
| Product group | Mechanical Cold Controls |
| Product name | Service kit |
| Quantity per packing format | 40 pc |
| Туре | B62 |
| Type designation | Service thermostat |
| Used for product | Refrigerators |
| | with automatic defrost |
| Warm cut-in [°C] | 3.5 ℃ |
| Warm cut-in [°F] | 38.3 °F |
| Warm cut-out [°C] | -11 °C |
| Warm cut-out [°F] | 12.2 °F |
| | |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.