



## 084B8521 🗷

## Refrig appliance control (TXV), EKC 202A

Function: 2 Outputs,2 Temp.Sensors, DI, Supply voltage [V] AC: 230, Communication type: Optional LON,; Optional MODBUS, Packing format: Multi pack, Quantity per packing format: 20

## **PRODUCT DETAILS**

Gross weight	0.22 kg
Net weight	0.2 kg
EAN	5702428081108
Application area	Refrigeration control
Approval	C-TICK
	CE
	EAC
	Intertek Semco
	cURus
Communication type	Optional LON,
	Optional MODBUS
Controller type	Refrig. Controller (Temp)
Display on front	Yes
Frequency [Hz]	50/60 Hz
Function	2 Outputs,2 Temp.Sensors, DI
Number of Compressors max.	1 pc
Number of Evaporators max.	1 pc
Packing format	Multi pack
Power consumption [VA]	1.5 VA
Product accessories	Electron. control accessories
Product group	Evaporator and room control
Product name	Refrig appliance control (TXV)
Quantity per packing format	20 pc
Serviceable	No
Supply voltage [V] AC	230 V
Temp. sensor support	NTC-M2020
	PTC 1000
	Pt 1000
Туре	EKC 202A

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.