



CCL-72-DN6-R744-TC

Item Number 4687906

High pressure hose for CO2 transcritical applications, connections on both sides 1/4" SAE

- High pressure resistant hose, working pressure up to static working pressure 160 bar
- Pressed Interlock fittings, according to standard DIN EN ISO 4413

Technical Data

Material	Brass Rubber
Colour	black
Number of Hoses	3
Length	180 cm
Sealing	PTFE
System Connection	1/4" SAE Straight
Device Connection	1/4" SAE
Valve Core Depressor	No
Ball Valve	No
Working Pressure	160 bar
Burst Pressure	800 bar
Standards	EN 853, EN 857, SAE J517-100 R1
Diameter	1/4"
Packaging	Blister

Accessories

4661147	CA-1/2"-20UNF-Y	Ball valve, yellow, 1/2"-20UNF X 1/2"-20UNF
---------	-----------------	---------------------------------------------

Acknowledged globally



4661121	CA-1/2"-20UNF-B	Ball valve, blue, 1/2"-20UNF X 1/2"-20UNF
4661139	CA-1/2"-20UNF-R	Ball valve, red, 1/2"-20UNF X 1/2"-20UNF
4682446	CA-1/2"-20UNF-Y-45°	Ball valve for charging hose, yellow with threaded hull 45° bent
4682420	CA-1/2"-20UNF-B-45°	Ball valve, blue with threaded hull 45° bent
4682438	CA-1/2"-20UNF-R-45°	Ball valve for charging hose, red with threaded hull 45° bent