

Model: AE4470Z-FZ3C
Product Description

Type:	Reciprocating Compressors
Application:	HBP/CBP - High/Commercial Back Pressure
Refrigerant:	R-404A
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-407A)	220V ~ 50HZ	6191	1561	1814	779	7.95	2	2.33	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-449A)	220V ~ 50HZ	6375	1607	1868	777	8.21	2.07	2.41	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-448A)	220V ~ 50HZ	6375	1607	1868	777	8.21	2.07	2.41	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-452A)	220V ~ 50HZ	6239	1573	1828	809	7.71	1.94	2.26	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-404A)	220V ~ 50HZ	6600	1663	1934	845	7.81	1.97	2.29	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	11
Weight Unit of Measure:	KG
Displacement (cc):	12.01
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	387

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	18.2
Rated Load Amps (RLA 50 Hz):	3.9
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.86
Motor Resistance (Ohm) - Start:	12.16
Motor Type:	CSR

Overload Type:

Relay Type:

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, VDE Listed