



COPPER CAPILLARY TUBE FINISHED PLAIN, COVERED WITH TIN AND/OR PLASTIC COATED, COPPER PRECISION FITTINGS AND TUBES TO NATIONAL, INTERNATIONAL AND CUSTOMER SPECIFICATIONS.

INSPECTION CERTIFICATE TYPE 3.1 (ref. EN 10204)	CERTIFICATE N°	85170		
	CUSTOMER	002997-DARMENT OY		
	NOMINAL SIZES mm	15,55 x 19,05		
	DRAWING NUMBER			
Sc N°: 85170 St N°: 3929	STANDARD REFERENCE	EN 12735-1/EN 378-2/ASTM B111		
	WORKING PRESSURE	Max 120 bar (R220; S.F. 3)		
	DENOMINATION	VERGHE		
	PRODUCT TYPE	GREEN 120BAR		
	PHYSICAL STATE	HARD		
	CUSTOMER'S ORDER NUMBER	3574		
	D.D.T. N°	10794	DATE	1.04.19

CHARACTERISTICS		REQUESTED		CHECKED
INSIDE DIAMETER	mm	15,55		15,62
OUTSIDE DIAMETER	mm	19,05 + 0,06 - 0,06		19,06
THICKNESS	mm	1,75		1,72
LENGTH	mm	5.000,00 + 5,00 - 0		CONFORMING
UNIT TENSILE STRENGTH	MPa	Min	290,00	456,00
ELONGATION	%	Min	3,00	4,00
HARDNESS	HV5	/		/
GRAIN SIZE	mm	/		/
CHEMICAL COMPOSITION	%	Cu+Ag = Min 99,90		99,96 *
(Copper type Cu-DHP)**	%	P = 0,015 ÷ 0,040		0,030 *
HUMIDITY	mg/m ²	Max	/	/
TOTAL INTERNAL RESIDUE	mg/m ²	Max	/	/
CARBON RESIDUE	mg/dm ²	Max	/	/
EDDY CURRENT TEST			/	CONFORMING
EXPANDING TEST			/	/
FLANGING TEST			/	/
BENDING TEST			/	/

THE TESTED PRODUCT IS IN CONFORMITY TO THE REQUESTED CHARACTERISTICS

DATE:

1.04.19 - Passirano Document issued in electronic form without the need of signature RdQ Feinrohren (matr. n°147)

* Average value (all the values measured were within the tolerance).

** Characteristic of end-of-life product: 100% recyclable copper.