

Designation	NJ6220Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	144HA01

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors R134a, R22)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	26.11	[cm ³] (1.593 cu.in)
2.1 Bore	41.770	
2.2 Stroke	9.533	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight(with oil charge)	20.5	[kg] (45.19 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device		
3 Start capacitor	88-108(330)	[µf(VAC minimum)]
4 Run capacitor	-	[µf(VAC minimum)]
5 Motor protection (external)	T0825/C9	
6 Start winding resistance	13.62	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.11	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature 7.2°C (44.96°F) (Condensing temperature 54.4°C (129.92°F))				
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
8692	2190	2547	978	5.71	56.36	8.89	2.24	2.60	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	3918	987	1148	567	4.40	21.22	6.88	1.73	2.02
-10	(+14)	4851	1222	1421	623	4.54	26.32	7.81	1.97	2.29
-5	(+23)	6149	1550	1802	676	4.69	33.47	9.12	2.30	2.67
0	(+32)	7814	1969	2290	724	4.83	42.73	10.79	2.72	3.16
+5	(+41)	9844	2481	2885	768	4.98	54.16	12.80	3.23	3.75
+10	(+50)	12240	3085	3587	809	5.12	67.79	15.13	3.81	4.43

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	3287	828	963	571	4.39	19.16	5.78	1.46	1.69
-10	(+14)	4321	1089	1266	645	4.60	25.35	6.70	1.69	1.96
-5	(+23)	5605	1412	1642	716	4.81	33.04	7.81	1.97	2.29
0	(+32)	7141	1799	2092	785	5.03	42.29	9.07	2.29	2.66
+5	(+41)	8928	2250	2616	852	5.26	53.15	10.47	2.64	3.07
+10	(+50)	10965	2763	3213	916	5.51	65.66	12.00	3.02	3.52

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2638	665	773	575	4.39	16.83	4.59	1.16	1.35
-10	(+14)	3767	949	1104	667	4.65	24.09	5.62	1.42	1.65
-5	(+23)	5032	1268	1475	758	4.93	32.31	6.63	1.67	1.94
0	(+32)	6434	1621	1885	849	5.24	41.53	7.61	1.92	2.23
+5	(+41)	7972	2009	2336	939	5.56	51.81	8.52	2.15	2.50
+10	(+50)	9646	2431	2827	1028	5.90	63.20	9.35	2.36	2.74

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard
2 Tray holder	No
3 Connectors	
3.1 SUCTION	9.6 +0.07/+0.00 [mm] (0.378" +0.003"/+0.000")
3.1.1 Material	Copper
3.1.2 Shape	Vertical
3.2 DISCHARGE	8 +0.07/+0.00 [mm] (0.315" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Slanted J
3.3 PROCESS	9.6 +0.07/+0.00 [mm] (0.378" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs