



**General Characteristics**

Model number (on compressor nameplate)		<b>NTZ136A4LR1B</b>
Code number for Singlepack*		120F0236
Code number for Industrial pack**		120F0237
Drawing number		8502012g
Suction and discharge connections		Rotolock
Suction connection		1-3/4" Rotolock
Discharge connection		1-1/4" Rotolock
Suction connection with supplied sleeve		1-1/8" ODF
Discharge connection with supplied sleeve		3/4" ODF
Oil sight glass		Threaded
Oil equalisation connection		3/8" flare SAE
Oil drain connection		None
LP gauge port		Schrader
IPR valve		30 bar / 8 bar
Cylinders		2
Swept volume		136 cm <sup>3</sup> /rev
Displacement @ Nominal speed		23.7 m <sup>3</sup> /h @ 2900 rpm - 28.6 m <sup>3</sup> /h @ 3500 rpm
Net weight		35 kg
Oil charge		1.8 litre, POE - 175PZ
Maximum system test pressure Low Side / High side		25 bar(g) / 30 bar(g)
Maximum differential test pressure		30 bar
Maximum number of starts per hour		12
Refrigerant charge limit		5 kg
Approved refrigerants		R404A, R452A

**Dimensions**


D=288 mm  
H=413 mm  
H1=265 mm  
H2=74 mm  
H3=- mm

**Terminal box**


IP55 (with cable gland)

- 1: Spade connectors 1/4"
- 2: Earth M4-12
- 3: Knock-out Ø 21 mm (0.83")
- 4: Hole Ø 21 mm (0.83")

**Electrical Characteristics**

Nominal voltage	380-400V/3/50Hz - 460V/3/60Hz
Voltage range	340-440 V @ 50Hz - 414-506 V @ 60Hz
Winding resistance (between phases) +/- 7% at 25°C	3.8 Ω
Maximum Continuous Current (MCC)	14.3 A
Locked Rotor Amps (LRA)	51 A
Motor protection	Internal overload protector

**Recommended Installation torques**

Oil sight glass	50 Nm
Power connections / Earth connection	2 Nm / 2 Nm
Mounting bolts	15 Nm

**Parts shipped with compressor**

Mounting kit with grommets, bolts, nuts, sleeves and washers
Suction & Discharge solder sleeves, rotolock nuts and gaskets (shipped with rotolock version only)
Initial oil charge
Installation instructions

**Approvals** : CE certified, -, -

\*Singlepack: Compressor in cardboard box


\*\*Industrial pack: 6 Unboxed compressors on pallet (order per multiples of 6)

**Rotolock accessories, suction side**

**Code no.**

Solder sleeve, P02 (1-3/4" Rotolock, 1-1/8" ODF)	8153004
Angle adapter, C02 (1-3/4" Rotolock, 1-1/8" ODF)	8168005
Rotolock valve, V02 (1-3/4" Rotolock, 1-1/8" ODF)	8168028
Gasket, 1-3/4"	8156132

**Gaskets, sleeves and nuts**



- 1: Gasket
- 2: Solder sleeve
- 3: Rotolock nut

**Rotolock accessories, discharge side**

**Code no.**

Solder sleeve, P04 (1-1/4" Rotolock, 3/4" ODF)	8153008
Angle adapter, C04 (1-1/4" Rotolock, 3/4" ODF)	8168006
Rotolock valve, V04 (1-1/4" Rotolock, 3/4" ODF)	8168029
Gasket, 1-1/4"	8156131

**Rotolock accessories, sets**

**Code no.**

Angle adapter set, C02 (1-3/4"~1-1/8"), C04 (1-1/4"~3/4")	7703014
Valve set, V02 (1-3/4"~1-1/8"), V04 (1-1/4"~3/4")	7703009
Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black & white	8156009

**Oil / lubricants**

**Code no.**


POE lubricant, 175PZ, 1 litre can	120Z0638
POE lubricant, 175PZ, 2.5 litre can	120Z0639

**Crankcase heaters**

**Code no.**

PTC heater 27W, CE mark, UL	120Z0459
Belt type crankcase heater, 65 W, 230 V, CE mark, UL	7773107
Belt type crankcase heater, 65 W, 400 V, CE mark, UL	7773117
Belt type crankcase heater, 65 W, 460 V, CE mark, UL	120Z0466

**Mounting kit**



- 1: Bolt (3x)
- 2: Lock washer (3x)
- 3: Flat washer (3x)
- 4: Sleeve (3x)
- 5: Grommet (3x)
- 6: Nut (3x)

**Miscellaneous accessories**

**Code no.**

Acoustic hood for 2 cylinder compressor	120Z0472
Oil equalisation nut	8153127

**Spare parts**

**Code no.**

Mounting kit for 1 and 2 cylinder compressor, including 3 grommets, 3 bolts	8156001
Oil sight glass with gaskets (black & white)	8156019
Gasket for oil sight glass (black chloroprene)	8156145
Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp	8156134

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alternations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss, the Danfoss logotype and Maneurop are trademarks of Danfoss A/S. All rights reserved.

**Performance data at 50 Hz, EN 12900 rating conditions, Suction temp. = 20 °C**
**R452A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	-	-	4 184	5 610	7 356	9 455	11 937	14 836	-
35	-	-	3 753	5 048	6 639	8 556	10 831	13 497	-
40	-	-	3 350	4 518	5 956	7 695	9 768	12 205	-
45	-	-	-	4 017	5 306	6 871	8 744	10 955	-
50	-	-	-	-	4 685	6 080	7 756	9 746	-
55	-	-	-	-	-	5 318	6 803	8 575	-
60	-	-	-	-	-	-	-	-	-

**Power input in W**

30	-	-	2 704	3 126	3 559	4 005	4 468	4 951	-
35	-	-	2 742	3 195	3 660	4 138	4 634	5 150	-
40	-	-	2 775	3 265	3 766	4 282	4 816	5 371	-
45	-	-	-	3 323	3 866	4 425	5 003	5 602	-
50	-	-	-	-	3 951	4 558	5 184	5 832	-
55	-	-	-	-	-	4 668	5 348	6 050	-
60	-	-	-	-	-	-	-	-	-

**Current consumption in A**

30	-	-	5.92	6.28	6.71	7.20	7.74	8.33	-
35	-	-	6.07	6.50	7.00	7.55	8.16	8.80	-
40	-	-	6.11	6.62	7.20	7.82	8.49	9.20	-
45	-	-	-	6.66	7.32	8.02	8.77	9.54	-
50	-	-	-	-	7.37	8.17	9.00	9.85	-
55	-	-	-	-	-	8.28	9.20	10.14	-
60	-	-	-	-	-	-	-	-	-

**Mass flow in kg/h**

30	-	-	101	135	178	230	293	367	-
35	-	-	95	128	169	219	280	351	-
40	-	-	90	121	161	209	267	336	-
45	-	-	-	115	152	198	254	321	-
50	-	-	-	-	144	188	242	307	-
55	-	-	-	-	-	179	230	292	-
60	-	-	-	-	-	-	-	-	-

**Coefficient of performance (C.O.P.)**

30	-	-	1.55	1.79	2.07	2.36	2.67	3.00	-
35	-	-	1.37	1.58	1.81	2.07	2.34	2.62	-
40	-	-	1.21	1.38	1.58	1.80	2.03	2.27	-
45	-	-	-	1.21	1.37	1.55	1.75	1.96	-
50	-	-	-	-	1.19	1.33	1.50	1.67	-
55	-	-	-	-	-	1.14	1.27	1.42	-
60	-	-	-	-	-	-	-	-	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	3 350	W
Power input	2 775	W
Current consumption	6.11	A
Mass flow	90	kg/h
C.O.P.	1.21	

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level		dB(A)
With acoustic hood		dB(A)

to: Evaporating temperature at dew point

tc: Condensing temperature at dew point

Rating conditions : Suction gas temp. = 20 °C , Subcooling = 0 K

Tolerance according EN12900

**Performance data at 50 Hz, EN 12900 rating conditions, Superheat = 10 K**
**R452A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	-	2 755	3 829	5 195	6 892	8 959	11 435	14 360	-
35	-	2 413	3 376	4 605	6 139	8 017	10 280	12 968	-
40	-	2 098	2 954	4 050	5 425	7 119	9 172	11 625	-
45	-	-	2 559	3 527	4 747	6 260	8 106	10 330	-
50	-	-	-	3 031	4 101	5 437	7 081	9 077	-
55	-	-	-	2 560	3 483	4 646	6 091	7 864	-
60	-	-	-	-	-	-	-	-	-

**Power input in W**

30	-	2 290	2 704	3 126	3 559	4 005	4 468	4 951	-
35	-	2 297	2 742	3 195	3 660	4 138	4 634	5 150	-
40	-	2 294	2 775	3 265	3 766	4 282	4 816	5 371	-
45	-	-	2 792	3 323	3 866	4 425	5 003	5 602	-
50	-	-	-	3 359	3 951	4 558	5 184	5 832	-
55	-	-	-	3 363	4 007	4 668	5 348	6 050	-
60	-	-	-	-	-	-	-	-	-

**Current consumption in A**

30	-	5.64	5.92	6.28	6.71	7.20	7.74	8.33	-
35	-	5.72	6.07	6.50	7.00	7.55	8.16	8.80	-
40	-	5.67	6.11	6.62	7.20	7.82	8.49	9.20	-
45	-	-	6.06	6.66	7.32	8.02	8.77	9.54	-
50	-	-	-	6.62	7.37	8.17	9.00	9.85	-
55	-	-	-	6.54	7.39	8.28	9.20	10.14	-
60	-	-	-	-	-	-	-	-	-

**Mass flow in kg/h**

30	-	90	122	161	208	263	328	403	-
35	-	85	115	152	197	251	314	387	-
40	-	80	108	144	187	239	300	370	-
45	-	-	102	136	177	227	286	354	-
50	-	-	-	128	168	215	272	337	-
55	-	-	-	121	159	204	258	322	-
60	-	-	-	-	-	-	-	-	-

**Coefficient of performance (C.O.P.)**

30	-	1.20	1.42	1.66	1.94	2.24	2.56	2.90	-
35	-	1.05	1.23	1.44	1.68	1.94	2.22	2.52	-
40	-	0.91	1.06	1.24	1.44	1.66	1.90	2.16	-
45	-	-	0.92	1.06	1.23	1.41	1.62	1.84	-
50	-	-	-	0.90	1.04	1.19	1.37	1.56	-
55	-	-	-	0.76	0.87	1.00	1.14	1.30	-
60	-	-	-	-	-	-	-	-	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	2 954	W
Power input	2 775	W
Current consumption	6.11	A
Mass flow	108	kg/h
C.O.P.	1.06	

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level		dB(A)
With acoustic hood		dB(A)

to: Evaporating temperature at dew point

tc: Condensing temperature at dew point

Rating conditions : Superheat = 10 K , Subcooling = 0 K

Tolerance according EN12900

Performance data at 50 Hz, EN 12900 rating conditions, Suction temp. = 20 °C

**R404A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	-	2 943	4 059	5 425	7 068	9 019	11 303	13 951	-
35	-	-	3 644	4 918	6 452	8 272	10 406	12 884	-
40	-	-	3 225	4 407	5 827	7 514	9 496	11 801	-
45	-	-	-	3 892	5 197	6 748	8 575	10 706	-
50	-	-	-	-	4 564	5 977	7 646	9 599	-
55	-	-	-	-	-	5 204	6 713	8 486	-
60	-	-	-	-	-	4 430	5 776	7 367	-

**Power input in W**

30	-	2 400	2 893	3 358	3 787	4 173	4 509	4 788	-
35	-	-	2 911	3 429	3 924	4 390	4 820	5 205	-
40	-	-	2 896	3 461	4 017	4 557	5 073	5 560	-
45	-	-	-	3 468	4 079	4 687	5 285	5 866	-
50	-	-	-	-	4 126	4 796	5 470	6 140	-
55	-	-	-	-	-	4 899	5 642	6 395	-
60	-	-	-	-	-	5 010	5 817	6 647	-

**Current consumption in A**

30	-	5.59	6.07	6.59	7.13	7.68	8.24	8.80	-
35	-	-	6.11	6.70	7.32	7.96	8.61	9.25	-
40	-	-	6.10	6.77	7.47	8.20	8.94	9.68	-
45	-	-	-	6.79	7.58	8.40	9.23	10.08	-
50	-	-	-	-	7.65	8.56	9.50	10.45	-
55	-	-	-	-	-	8.69	9.73	10.79	-
60	-	-	-	-	-	8.78	9.94	11.11	-

**Mass flow in kg/h**

30	-	71	98	131	172	221	279	348	-
35	-	-	93	126	166	214	272	339	-
40	-	-	87	120	159	207	263	331	-
45	-	-	-	113	152	199	255	321	-
50	-	-	-	-	144	190	245	311	-
55	-	-	-	-	-	181	235	300	-
60	-	-	-	-	-	170	224	288	-

**Coefficient of performance (C.O.P.)**

30	-	1.23	1.40	1.62	1.87	2.16	2.51	2.91	-
35	-	-	1.25	1.43	1.64	1.88	2.16	2.48	-
40	-	-	1.11	1.27	1.45	1.65	1.87	2.12	-
45	-	-	-	1.12	1.27	1.44	1.62	1.82	-
50	-	-	-	-	1.11	1.25	1.40	1.56	-
55	-	-	-	-	-	1.06	1.19	1.33	-
60	-	-	-	-	-	0.88	0.99	1.11	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	3 225	W
Power input	2 896	W
Current consumption	6.10	A
Mass flow	87	kg/h
C.O.P.	1.11	



to: Evaporating temperature at dew point  
 tc: Condensing temperature at dew point  
 Rating conditions : Suction gas temp. = 20 °C , Subcooling = 0 K

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level	77.3	dB(A)
With acoustic hood	71.3	dB(A)

Tolerance according EN12900

**Performance data at 50 Hz, EN 12900 rating conditions, Superheat = 10 K**
**R404A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	1 796	2 617	3 661	4 961	6 552	8 469	10 749	13 426	-
35	1 502	2 261	3 223	4 421	5 891	7 669	9 790	12 293	-
40	-	1 911	2 788	3 882	5 228	6 862	8 823	11 147	-
45	-	1 570	2 359	3 346	4 565	6 053	7 848	9 992	-
50	-	1 243	1 941	2 817	3 905	5 243	6 871	8 828	-
55	-	-	1 536	2 298	3 252	4 437	5 891	7 659	-
60	-	-	-	1 793	2 609	3 635	4 911	6 483	-

**Power input in W**

30	1 885	2 400	2 893	3 358	3 787	4 173	4 509	4 788	-
35	1 837	2 378	2 911	3 429	3 924	4 390	4 820	5 205	-
40	-	2 329	2 896	3 461	4 017	4 557	5 073	5 560	-
45	-	2 268	2 862	3 468	4 079	4 687	5 285	5 866	-
50	-	2 209	2 825	3 467	4 126	4 796	5 470	6 140	-
55	-	-	2 800	3 471	4 173	4 899	5 642	6 395	-
60	-	-	-	3 495	4 234	5 010	5 817	6 647	-

**Current consumption in A**

30	5.15	5.59	6.07	6.59	7.13	7.68	8.24	8.80	-
35	5.05	5.56	6.11	6.70	7.32	7.96	8.61	9.25	-
40	-	5.47	6.10	6.77	7.47	8.20	8.94	9.68	-
45	-	5.32	6.03	6.79	7.58	8.40	9.23	10.08	-
50	-	5.11	5.91	6.76	7.65	8.56	9.50	10.45	-
55	-	-	5.74	6.68	7.67	8.69	9.73	10.79	-
60	-	-	-	6.56	7.65	8.78	9.94	11.11	-

**Mass flow in kg/h**

30	62	88	119	156	201	253	314	384	-
35	56	82	113	150	194	246	306	375	-
40	-	75	106	143	186	237	297	365	-
45	-	68	98	134	177	228	287	354	-
50	-	60	90	126	168	218	276	343	-
55	-	-	81	116	158	207	265	331	-
60	-	-	-	106	147	196	252	317	-

**Coefficient of performance (C.O.P.)**

30	0.95	1.09	1.27	1.48	1.73	2.03	2.38	2.80	-
35	0.82	0.95	1.11	1.29	1.50	1.75	2.03	2.36	-
40	-	0.82	0.96	1.12	1.30	1.51	1.74	2.01	-
45	-	0.69	0.82	0.96	1.12	1.29	1.49	1.70	-
50	-	0.56	0.69	0.81	0.95	1.09	1.26	1.44	-
55	-	-	0.55	0.66	0.78	0.91	1.04	1.20	-
60	-	-	-	0.51	0.62	0.73	0.84	0.98	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	2 788	W
Power input	2 896	W
Current consumption	6.10	A
Mass flow	106	kg/h
C.O.P.	0.96	

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level	77.3	dB(A)
With acoustic hood	71.3	dB(A)

to: Evaporating temperature at dew point

tc: Condensing temperature at dew point

Rating conditions : Superheat = 10 K , Subcooling = 0 K

Tolerance according EN12900

**Performance data at 60 Hz, EN 12900 rating conditions, Suction temp. = 20 °C**
**R404A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	-	3 325	4 739	6 437	8 446	10 795	13 512	16 626	-
35	-	-	4 244	5 844	7 734	9 942	12 496	15 425	-
40	-	-	3 739	5 237	7 003	9 064	11 450	14 189	-
45	-	-	-	4 621	6 258	8 168	10 380	12 924	-
50	-	-	-	-	5 503	7 257	9 291	11 634	-
55	-	-	-	-	-	6 336	8 187	10 324	-
60	-	-	-	-	-	5 411	7 072	8 999	-

**Power input in W**

30	-	2 793	3 360	3 954	4 570	5 203	5 847	6 498	-
35	-	-	3 365	4 000	4 665	5 355	6 064	6 787	-
40	-	-	3 351	4 028	4 742	5 489	6 263	7 059	-
45	-	-	-	4 032	4 796	5 600	6 440	7 308	-
50	-	-	-	-	4 821	5 683	6 587	7 529	-
55	-	-	-	-	-	5 731	6 702	7 717	-
60	-	-	-	-	-	5 741	6 777	7 866	-

**Current consumption in A**

30	-	5.11	5.69	6.31	6.96	7.60	8.23	8.80	-
35	-	-	5.70	6.40	7.13	7.87	8.60	9.30	-
40	-	-	5.67	6.44	7.26	8.10	8.95	9.78	-
45	-	-	-	6.44	7.35	8.30	9.26	10.22	-
50	-	-	-	-	7.39	8.44	9.52	10.61	-
55	-	-	-	-	-	8.52	9.72	10.95	-
60	-	-	-	-	-	8.53	9.86	11.22	-

**Mass flow in kg/h**

30	-	80	115	156	205	264	333	414	-
35	-	-	108	149	199	257	326	406	-
40	-	-	101	142	191	249	318	398	-
45	-	-	-	134	183	240	308	388	-
50	-	-	-	-	173	231	298	377	-
55	-	-	-	-	-	220	287	365	-
60	-	-	-	-	-	208	274	351	-

**Coefficient of performance (C.O.P.)**

30	-	1.19	1.41	1.63	1.85	2.07	2.31	2.56	-
35	-	-	1.26	1.46	1.66	1.86	2.06	2.27	-
40	-	-	1.12	1.30	1.48	1.65	1.83	2.01	-
45	-	-	-	1.15	1.30	1.46	1.61	1.77	-
50	-	-	-	-	1.14	1.28	1.41	1.55	-
55	-	-	-	-	-	1.11	1.22	1.34	-
60	-	-	-	-	-	0.94	1.04	1.14	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	3 739	W
Power input	3 351	W
Current consumption	5.67	A
Mass flow	101	kg/h
C.O.P.	1.12	

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level	84.2	dB(A)
With acoustic hood	77	dB(A)

to: Evaporating temperature at dew point

tc: Condensing temperature at dew point

Rating conditions : Suction gas temp. = 20 °C , Subcooling = 0 K

Tolerance according EN12900

**Performance data at 60 Hz, EN 12900 rating conditions, Superheat = 10 K**
**R404A**

Cond. temp. in °C (tc)	Evaporating temperature in °C (to)							
	-45	-40	-35	-30	-25	-20	-15	-10

**Cooling capacity in W**

30	1 899	2 957	4 275	5 887	7 829	10 137	12 849	16 000	-
35	1 539	2 527	3 754	5 253	7 062	9 217	11 756	14 717	-
40	-	2 103	3 232	4 613	6 283	8 278	10 639	13 403	-
45	-	1 690	2 716	3 972	5 497	7 326	9 501	12 062	-
50	-	1 297	2 212	3 337	4 709	6 366	8 349	10 699	-
55	-	-	1 726	2 713	3 926	5 403	7 185	9 318	-
60	-	-	-	2 106	3 151	4 439	6 013	7 919	-

**Power input in W**

30	2 260	2 793	3 360	3 954	4 570	5 203	5 847	6 498	-
35	2 205	2 765	3 365	4 000	4 665	5 355	6 064	6 787	-
40	-	2 717	3 351	4 028	4 742	5 489	6 263	7 059	-
45	-	2 646	3 313	4 032	4 796	5 600	6 440	7 308	-
50	-	2 545	3 247	4 007	4 821	5 683	6 587	7 529	-
55	-	-	3 146	3 948	4 812	5 731	6 702	7 717	-
60	-	-	-	3 850	4 764	5 741	6 777	7 866	-

**Current consumption in A**

30	4.59	5.11	5.69	6.31	6.96	7.60	8.23	8.80	-
35	4.49	5.06	5.70	6.40	7.13	7.87	8.60	9.30	-
40	-	4.97	5.67	6.44	7.26	8.10	8.95	9.78	-
45	-	4.83	5.59	6.44	7.35	8.30	9.26	10.22	-
50	-	4.62	5.46	6.39	7.39	8.44	9.52	10.61	-
55	-	-	5.25	6.26	7.36	8.52	9.72	10.95	-
60	-	-	-	6.06	7.26	8.53	9.86	11.22	-

**Mass flow in kg/h**

30	65	99	139	186	240	303	375	457	-
35	57	91	131	178	232	295	367	449	-
40	-	83	123	169	224	286	358	439	-
45	-	73	113	160	214	276	347	428	-
50	-	63	103	149	203	265	336	416	-
55	-	-	91	137	191	252	323	402	-
60	-	-	-	125	178	239	309	388	-

**Coefficient of performance (C.O.P.)**

30	0.84	1.06	1.27	1.49	1.71	1.95	2.20	2.46	-
35	0.70	0.91	1.12	1.31	1.51	1.72	1.94	2.17	-
40	-	0.77	0.96	1.15	1.32	1.51	1.70	1.90	-
45	-	0.64	0.82	0.99	1.15	1.31	1.48	1.65	-
50	-	0.51	0.68	0.83	0.98	1.12	1.27	1.42	-
55	-	-	0.55	0.69	0.82	0.94	1.07	1.21	-
60	-	-	-	0.55	0.66	0.77	0.89	1.01	-

**Nominal performance at to = -35 °C, tc = 40 °C**

Cooling capacity	3 232	W
Power input	3 351	W
Current consumption	5.67	A
Mass flow	123	kg/h
C.O.P.	0.96	

**Pressure switch settings**

Maximum HP switch setting	27.7	bar(g)
Minimum LP switch setting	0.1	bar(g)
LP pump down setting	0.1	bar(g)

**Sound power data**

Sound power level	84.2	dB(A)
With acoustic hood	77	dB(A)

to: Evaporating temperature at dew point

tc: Condensing temperature at dew point

Rating conditions : Superheat = 10 K , Subcooling = 0 K

Tolerance according EN12900