

	Unit model			WV583137	
	Compressor			AE4470Z	
	Power supply		[V/ph/Hz]	230/1/50	
	Refrigerant			R452A/R448A/R449A	
	Dimensions	width	[mm]	390	
		depth	[mm]	480	
		height	[mm]	270	
	Accessories	water pressostatic valve			AWR1203
		liquid receiver			2,5 L
		cooling fan			Ø 200
		tube in tube water condenser			CHS2/S-P
		double pressure switch			PS15AAL-S01
	Connections	high pressure relief device			no
		liquid	[Ø]		6
		suction	[Ø]		10
	UNIT PERFORMANCE		water	[Ø]	3/8"
		I MAX		[A]	3,9
P MAX			[W]	834	
T-in water			[°C]	15	
T-cond			[°C]	35	
cooling capacity T _{evap} =-10°C +35°C cond EN12900		R452A	[W]		1153
cooling capacity T _{evap} =-10°C +35°C cond EN12900		R448A / R449A	[W]		1080

compressor
 basement in galvanized metal sheet
 tube-in-tube water condenser
 compressor cooling fan
 double pressure switch
 liquid receiver (with safety valve on larger models)
 liquid and suction valve
 2 m power cable for single-phase models
 empty and not wired box for three-phase models
 pressostatic water valve

