

	Unit model			WV1503137	
	Compressor			CAJ4519Z	
	Power supply		[V/ph/Hz]	230/1/50	
	Refrigerant			R452A/R448A/R449A	
	Dimensions	width	[mm]	450	
		depth	[mm]	540	
		height	[mm]	395	
	Accessories	water pressostatic valve			AWR1504
		liquid receiver			5,2 L
		cooling fan			Ø 200
		tube in tube water condenser			CHS4/S-P
		double pressure switch			PS15AAL-S01
	Connections	high pressure relief device			yes
		liquid	[Ø]		10
		suction	[Ø]		16
		water	[Ø]		1/2"
UNIT PERFORMANCE	I MAX		[A]	10,12	
	P MAX		[W]	2211	
	T-in water		[°C]	15	
	T-cond		[°C]	35	
	cooling capacity Tevap=-10°C +35°C cond EN12900	R452A		[W]	3199
	cooling capacity Tevap=-10°C +35°C cond EN12900	R448A / R449A		[W]	2998

compressor  
basement in galvanized metal sheet  
tube-in-tube water condenser  
compressor cooling fan  
double pressure switch  
liquid receiver (with safety valve on larger models)  
liquid and suction valve  
2 m power cable for single-phase models  
empty and not wired box for three-phase models  
pressostatic water valve

